#### 'APPROVED FOR RELEASE: 08/25/2000 ATTERNET PRODUCTION OF THE PARTY HAVE AND REAL PROPERTY.

CIA-RDP86-00513R001549420003-3

L 10037-67 EWP(j) SOURCE CODE: UR/0342/65/000/012/0057/0059 ACC NR: AP6014698

Shikher, M. G. (Associate); Yezhova, Z. P. (Associate); Rybkina, L. A. AUTHOR: (Associate)

ORG: Ivanov Scientific Research Institute of the Cotton Industry IvNITI (Ivanovskiy nauchno-issledovatel'skiy institut khlopchatobumazhnoy promyshlennosti IvNITI)

TITIE: Bleaching with per acids

SOURCE: Tekstil'naya promyshlennost', no. 12, 1965, 57-59

TOPIC TAGS: toxtile, poroxy organic acid, bleaching powder

ABSTRACT: Some of the problems of bleaching with per acids by the continuous saturation-steaming method were examined using desized and scoured cambric. The fabric can be bleached with peracetic acid at not too high temperatures (60-70°C) to moderate whiteness which is retained, but little soil removal is effected. More whiteness is obtained with peracetic acid at low pH, but its stability is less than in hydrogen poroxide bleached fabric. Scoured fabric is bleached more easily than unscoured. Capillary properties are readily attained by bleaching at low temperatures. Peracetic acid bloaching at 100°C causes substantial destruction of the fabric cellulose, hence it cannot be used at high temperatures, and at low temperatures it does not meet the oxidizing and surface active requirements for bleaching desized cotton fabric. Orig. art. has: 4 tables. SUB CODE: 11, 13/ SUEM DATE: none/ ORIG REF: 677.064-12:677.826

			<u></u>	
SHIMMER, O. S.			8	
"Discoloration of Lead	d Grystal, in Glass	Production," Leg. Prom	% No. 4, 1947. Engr.	
···				

APPROVED FOR RELEASE: 08/25/2000 CIA-RDP86-00513R001549420003-3"

FATEYEV, Ivan Mikolayevich; RABINOVICH, E.A., red.; SHIKHER, S.M., red.; VORONIN, K.P., tekhn.red.

[Electric power; popular study] Elektroenergetika; populisrnyi ocherk. Moskva, Gos.energ.ivd-vo, 1960. 215 p.

(Electric power)

(Electric power)

SHIKHEYEVA, L.V.

Composition of compounds formed during the extraction of cobalt(11) by naphthenic acids. Zhur. neorg. khim. 10 no.6: 1486-1489 Je '65. (MIRA 18:6)

NESHUMOV, B.V., kand.iskusstvoved.nauk; KOSHELEV, A.Ye., arkhitektor; ASTROVA, T.Ye., arkhitektor; SHIKHEYEV, V.M., arkhitektor; VOSHCHANOVA, G.K., arkhitektor; GORBUNOVA, V.A., arkhitektor; KOVAL'KOV, V.G., arkhitektor; MARKEYEV, Yu.S., arkhitektor; YAVOROVSKAYA, M.E., arkhitektor; OGRYZKO, P.V., arkhitektor; TIKHONOVA, N.V., arkhitektor; MANANNIKOVA, L.V., arkhitektor; GRADOV, G.A., red.; PAVLENKO, M.V., red.

[Furniture and equipment for public buildings; catalog based on materials from the Exhibition of Furniture and Equipment for Public Buildings, 1959-1960] Mebel' i oborudovanie dlia obshchestvennykh zdanii; katalog sostavlen po materialam vystavki mebeli i oborudovaniia dlia obshchestvennykh zdanii, 1959-1960 gg. Moskva, Gos.izd-vo lit-ry po stroit., arkhit. i stroit.materialam, 1960. 186 plates. (MIRA 14:2)

STREET, STREET,

1. Akademiya stroitel'stva i arkhitektury SSSR. Institut obshchestvennykh zdaniy i sooruzheniy. 2. Chlen-korrespondent Akademii stroitel'stva i arkhitektury SSSR (for Gradov). (Furniture--Catalogs) (Public buildings--Equipment and supplies)

507/78-3-11-12/23 Grincers, A. A., Shikheyeva, L. V. The Oxidation of Complex Titanium Oxalates in the Potentiometric Titration (Okislitel noye potentsiometricheskoye AUTHORS: titrovaniye kompleksnykh oksalatov titana) Zhurnal neorganicheskoy khimii, 1958, Vol 3, Nr 11, TITLE: The oxidation of the compounds  $K_2[TiO(C_2O_4)_2]$ .  $2H_2O$ ,  $K[Ti(C_2O_4)_2]$ .  $2H_2O$  and  $E_2O$  and  $E_2O$ pp 2491 - 2495 (USSR) PERIODICAL: investigated. The method of the synthesis of the above mentioned compounds was given. The potentioned compounds with K Mn O was carried out at 35-7000 of these compounds with K Mn O was carried out at 35-7000 of these compounds with K Mn O was carried out at 35-7000 of these compounds with K Mn O was carried out at 35-7000 of these compounds with K Mn O was carried out at 35-7000 of these compounds with K Mn O was carried out at 35-7000 of these compounds with K Mn O was carried out at 35-7000 of these compounds with K Mn O was carried out at 35-7000 of these compounds with K Mn O was carried out at 35-7000 of these compounds with K Mn O was carried out at 35-7000 of these compounds with K Mn O was carried out at 35-7000 of these compounds with K Mn O was carried out at 35-7000 of these compounds with K Mn O was carried out at 35-7000 of these compounds with K Mn O was carried out at 35-7000 of these compounds with K Mn O was carried out at 35-7000 of these compounds with K Mn O was carried out at 35-7000 of these compounds with K Mn O was carried out at 35-7000 of these compounds with K Mn O was carried out at 35-7000 of these compounds with K Mn O was carried out at 35-7000 of these compounds with K Mn O was carried out at 35-7000 of the 35-700 ABSTRACT: of these compounds with K Mn O4 was carried out at 35-70°C and a potentiometric titration curve was plotted. The and a potentiometric titration curve was protted. The curve of  $K_2[TiO(C_2O_4)_2].2H_2O$  was investigated in dependence on the acidity of the solution; it showed a jump which corresponds to the oxidation of the oxalate group. The Corresponds to the oxidation of the oxalate group. The potentiometric titration curve of the compound potentiometric titration two jumps. The oxidation of the K  $\left[\text{Ti}\left(\text{C}_{2}\text{O}_{4}\right)_{2}\right]$  .2H<sub>2</sub>O has two jumps. card 1/3

The Oxidation of Complex Titanium Oxalates in the SOV/78-3-11-12/23 Potentiometric Titration compound  $K_2[Ti0(C_2O_4)_2]$ .  $2H_2O$  proceeds according to the following scheme:  $5K_2[\text{TiO(C}_2O_4)_2] + 4KMnO_4 + 16H_2SO_4 = 4MnSO_4 + 5TiOSO_4 + 20.CO_2 + 4MnSO_4 + 20.CO_2 + 4MnSO_4$ + 7K2SO4+16H2O. The first stage of the oxidation of  $K[Ti(c_2, c_4)_2]$ .  $2H_2O$  is the following: +  $3K_2SO_4$ . The gross-reaction of the oxidation of [Pt(NH<sub>3</sub>)<sub>4</sub>][TiO(C<sub>2</sub>O<sub>4</sub>)<sub>2</sub>]. 2H<sub>2</sub>O at 55°C proceeds according to the following scheme:  $5[Pt(NH_3)_4][TiO(C_2O_4)] + 6KMnO_4 + 19H_2SO_4 = 6MnSO_4 + +5[Pt(NH_3)_4(OH)_2]SO_4 + 20.CO_2 + 5TiOSO_4 + 3K_2SO_4 + 14H_2O.$  The results show that no separation of the titrated oxalate groups takes place in the complex oxalate compounds of the trivalent and tetravalent titanium. A gradual oxidation Card 2/3 of the oxalate groups was found only in the complex

The Oxidation of Complex Titanium Oxalates in the Potentiometric Titration

CALL OF THE PROPERTY AND ASSESSMENT OF THE PROPERTY OF THE PRO

SOV/78-3-11-12/23

£

compounds with platinum. There are 3 figures and 10 references, 8 of which are Soviet.

SUBMITTED:

July 18, 1957

Card 3/3

69052

572620 AUTHORS:

Grinberg, A. A., Shikneyeva, L. V.

S/078/60/005/03/016/048

B004/B002

TITLE:

The Stability of Complex Titanyloxalate in Solutions

PERIODICAL:
ABSTRACT:

Zhurnal neorganicheskoy khimii, 1960, Vol 5, Nr 3, pp 599-603 (USSR)

The authors refer to a paper by B. V. Ptitsyn and L. I. Vinogradova (Ref 1) who determined the instability constant of  $[Fe(C_2O_4)_3]^{3-1}$ 

by means of an oxalate-silver electrode, and state the reasons for having chosen an oxalate-mercury electrode. The instability constant of  $\left[\text{TiO}(\text{C}_2\text{O}_4)_2\right]^{\frac{1}{2}}$  was determined by means of a potentiometric

titration with HCl and by determining the oxalate ion by means of an oxalate-mercury electrode. The authors specify the six equilibria existing in the solution of potassium titanyl oxalate. In their investigation they chose the following equilibria for determining

the first instability constant  $K_1$ , namely  $\left[\text{TiO}(C_2O_4)(H_2O)_2\right] + 2H_2O \longrightarrow \left[\text{TiO}(H_2O)_4\right]^{2+} + C_2O_4^{2-}$  and

 $\begin{bmatrix} \text{TiO}(C_2O_4)_2 \end{bmatrix}^{2-} + 2H_2O \stackrel{}{=} \begin{bmatrix} \text{TiO}(C_2)_4(H_2O)_2 \end{bmatrix} + C_2O_4^{2-} \text{ for determining} \\ \text{the second instability constant } K_2. \text{ Since the solution of the} \end{bmatrix}$ 

Card 1/2

complex titanyl oxalate reaction is acid, only a slight correction

69052

The Stability of Complex Titanyloxalate in Solutions

S/078/60/005/03/016/048 B004/B002

of the instability constant is necessary. Experimental data are given in table 1. Table 2 gives the concentrations calculated for the complexes and the C<sub>2</sub>O<sub>4</sub><sup>2</sup> ions, and also the values of K<sub>2</sub>. The mean value found was K<sub>2</sub> = 0.77.10<sup>-5</sup>. The values obtained by potentiometric titration with HCl, were examined by means of an oxalatemercury electrode. Calibration of the electrode by means of potassium oxalate is described. Experimental results are shown in table 3. Table 4 gives the concentrations and values computed as to K<sub>2</sub>.

K<sub>2</sub> = 4.1.10<sup>-5</sup>. The determination of K<sub>1</sub> was made indirectly on the basis of the general instability constant K<sub>gen</sub> which by means of potentiometric titration with lye according to Bose (Ref 5), was found to be 1.5.10<sup>-15</sup>. Hence, K<sub>1</sub> was computed to be 2.10<sup>-10</sup>. A. K. Babko and L. I. Dubovenko (Ref 6) spectrophotometrically determined investigations. There are 4 tables and 9 references, 6 of which are Soviet.

SUBMITTED: Card 2/2

November 25, 1958

S/080/62/035/004/015/022 D244/D301

16.9-01

AUTHORS: Yakubchik, A. I., Shostatskaya, I. D., Shikheyeva, L.

V. and Vlasova, V. M.

TITLE:

Structure of butadiene - 1,3 polymers obtained in the

presence of Ziegler type catalyst

PERIODICAL: Zhurnal prikladnoy khimii, v. 35, no. 4, 1962, 876-880

TEXT: The authors investigated butadiene - 1,3 polymers obtained in the presence of:  $Al(C_2H_5)_2Cl + TiCl_4$  in the ratio of 3:1, and (2)  $Al(\underline{iso}-C_4H_9)_3 + TiCl_4$  in the ratio of 2:1. Attention was paid to the amount and distribution of the 1,2 and 1,4 bonds in the chains and the secondary reactions of branching and combination. The polymer samples were subjected to ozonolysis in methyl acetate solution and the acids obtained were separated by chromatography. The polymers obtained in the presence of the catalyst mixture had relatively evenly distributed 1,2 and 1,4 links in the macromolecules, as there were no acids with more than 3 carboxylic groups Card 1/2

Structure of butadiene ...

S/080/62/035/004/015/022 D244/D301

per molecule. The amount of 1,2 links varied within the limits 1.6-6.1%. There was no clear dependence of the amount of portions 1,4 -1,2 - 1,4 on the conditions of polymerization, Also no branching was found for the (-methyl group in link 1,4, since the acids obtained did not contain 1,2,3 propanetricarboxylic acid. There are 1 figure, 5 tables and 4 references: 3 Soviet-bloc and 1 non-Sovietbloc. The reference to the English-language publication reads as follows: C. S. Marvel, J. Org. Ch., 16, 838, (1951).

SUBMITTED: February 6, 1961

Card 2/2

SHIKHIN, Yu. S.

"On the Problems of Modeling Tectonic Phenomena," physicists L. M. Kachanov, Ye. I. Edel'shteyn, G. V. Vinogradov, G. N. Kuznetsov, M. P. Volarovich, and A. V. Stepanov and geologists F. I. Vol'fson, V. A. Aprodov, N. I. Borodayevskiy, and Yu. S. Shikhin

paper presented at the First All-Union Conference on Tectonophysics, Moscow 29 Jan - 5 Feb 1957.

Sum 15623 1563

#### SHIKHIN, Yu.S.

Determining the location of the hidden structural control of ores in the Koytash ore deposit. Geol.rud.mestorozh. no.5:80-103 S-0 '61. (MIRA 14:9)

1. Karamazarskaya poiskovo-s"yemochnaya tematicheskaya ekspeditsiya. (Nura-Tau--Ore deposits--Maps)

8(2)

AUTHOR:

Shikhin, Anatoliy Yakovlevich,

507/161-58-2-26/30

Assistant, Chair for General Electrical Engineering,

Moscow Power Engineering Institute

TITLE:

Increase of the Performance of Fekhral Resistances in Ventilation by Air Current (Uvelicheniye moshchnosti elementov fekhralevykh soprotivleniy pri obduve potokom

PERIODICAL:

Nauchnyye doklady vysshey shkoly. Elektromekhanika i

avtomatika, 1958, Nr 2, pp 209-216 (USSR)

ABSTRACT:

For Diesel locomotives and gas turbine locomotives electrodynamic braking is applied. As the brake resistances occupy much room, it is important to increase the performance of these individual resistance elements. In the present paper

this question is investigated and the brake resistances thermal state analyzed in order to select the most favorable cooling and construction system. Testing of the Fekhral' elements with ventilation cooling was performed at the

kafedra elektricheskogo transporta MEI (Chair for Electrical Transportation of the Moscow Energy Institute. A method of

Card 1/2

calculating the brake resistances is shown, which permits

Increase of the Performance of Fekhral' Resistances SCV/161-58-2-26/30 in Ventilation by Air Current

temporary calculation of performance and heating up of resistances as dependent on blowing intensity, environmental temperature and design of resistances, with sufficient accuracy. Examples are given which show that a certain number of rows of resistances can be placed in the air-flow direction if the resistances have their admissible air discharge temperature and admissible overheating of resistances. In order to reduce the size of the entire plant, it is expedient to use a two-way fan with driving electromotor. There are 6 figures and 5 references, 4 cf which are Soviet.

ASSOCIATION:

Kafedra obshchey elektrotekhniki Moskovskogo energeticheskogo instituta (Chair for General Electrical Englicering of Moscow Power

Engineering Institute)

SUBMITTED:

January 14, 1958

Card 2/2

8(5), 8(2), 12(3)

SOV/105-59-5-8/29

AUTHORS:

Nekrasov, O. A.; Candidate of Technical Sciences, Shikhin, A. Ya.,

Engineer

TITLE:

Self-regulation of Diesel Locomotive Generators Using Magnetic

Amplifiers (O samoregulirovanii teplovoznykh generatorov s

ispol'zovaniyem magnitnykh usiliteley)

PERIODICAL:

Elektrichestvo, 1959, Nr 5, pp 31-36 (USSR)

ABSTRACT:

In connection with the production of new heavy Diesel locomotives in the USSR, great attention is being paid to the problem

of self-regulation of generators with the use of magnetic amplifiers. On Diesel locomotives the generator excitation is produced by direct-current exciters. It is shown here that the use of a synchronous exciter instead of the direct-current exciter greatly reduces the spreading of self-regulation, and offers a possibility of reducing the amplifying coefficient and the capacity of the system for the automatic regulation of the capacity of the Diesel engine and of the generator. But the stability of the automatic regulation is also affected by other

Card 1/3

factors. The problem of stability with the use of a synchronous

SOV/105-59-5-8/29

Self-regulation of Diesel Locomotive Generators Using Magnetic Amplifiers

STATE OF THE STATE

exciter is investigated here, and the analytical correlations between the properties of self-regulation and the properties of the individual building groups of the wiring are determined in a general form. This general correlation is ascertained by means of an example for a special case of combination of certain building groups. A method of obtaining this correlation is but not given here. The correlation obtained is then generalized .-On the basis of this general method, some variants of wirings and combinations of building groups of the regulating systems for the generators of Diesel licemetives were investigated theoretically and in practice .- The investigation of the system at a reduced number of revolutions of the Diesel, and the calculation of the necessary properties of the regulation building groups were also carried out on the basis of the general correlations given here. The experimental control in the laboratory is described. The general correlations given for systems of self-regulation of generators for Diesel locomotives with the use of magnetic amplifiers make it possible to investigate wirings, and to carry out technical calculations of stationary operating conditions. The correlations obtained can also be

Card 2/3

SOV/105-59-5-8/29 Self-regulation of Diesel Locomotive Generators Using Magnetic Amplifiers

used for other drives in a generator-d.c.motor system. There

are 6 figures and 3 references, 1 of which is Soviet.

Moskovskiy energeticheskiy institut (Moscow Power Engineering

Institute)

SUBMITTED: January 31, 1959

Card 3/3

ASSOCIATION:

STEPANOV, A.D., doktor tekhn.nauk; SHIKHIN, A.Ya., inzh.

Regulating the generators of diesel locomotives by means of magnetic amplifiers. Vest. elektroprom. 31 no.5:44-47 My 160.

(MIRA 13:8)

(Diesel locomotives)

(Magnetic amplifiers)

(Electric generators)

SHIKHIN, Anatoliy Yakovlevich, assistent

Automatic control of the power and the electric current of the generator of a diesel locomotive. Izv. vys. ucheb. zav.; elektromekh. 4 no.9:56-69 161. (MIRA 14:9)

1. Mcskovskiy energeticheskiy institut.
(Diesel locomotives) (Electric generators)

SHIKHIN, A. YA.

S/271/63/000/001/017/047 D413/D308

· AUTHORS:

Nekrasov, O.A. and Snikhin, A.Ya.

TITLE:

On the calculation of operating range for automatic control systems for diesel locomotive electric trans-

missions

PERIODICAL:

Referativnyy zhurnal, Avtomatika, telemekhanika i vychislitel'naya tekhnika, no. 1, 1963, 45, abstract 1A248 (Tr. Mosk. energ. in-ta, no. 37, 1961, 75-85)

od for calculating the required variation of magnetizing force  $F_{\rm M}$  to drive the DC split-pole exciter used on Soviet diesel locomotives to achieve generator self-regulation for constant diesel power. A certain range of variation of magnetizing force is necessary to compensate for a considerable spread in self-regulation characteristics, and is secured by the systems of automatic control of power and current. The calculation is based on the technical data of the machines, exciter circuit diagrams of the diesel locomotive and families of

Card 1/2

On the calculation ...

\$/271/63/000/001/017/047

exciter load curves. These curves are obtained with the generator exciter windings both hot and cold, for a number of independent exciter winding current I; with one fixed value of shunt exciter winding current Is. Using the exciter load curves, a plot of exciter voltage against magnetizing force UE (FM) is constructed (for a given value of Ii and generator exciter winding impedance). The actual self-regulation characteristic is derived graphically by finding the intersection points of the curve of exciter voltage against magnetizing force (constructed from the exciter load curves) and the curve of magnetizing force against exciter volts obtained by considering the exciter circuit diagram. An example of the calculation is given. Self-regulation characteristics obtained in practice are stated to have agreed with the calculated one to an accuracy of about 3%. 4 figures. 1 reference. / Abstracter's note: Complete translation /

SHIKHIN, Anatoliy Yakovlevich, assistent; ANDERS, Vitaliy Ivanovich, assistent

Design of magnetic amplifiers with internal feedback. Izv. vys. ucheb. zav.; elektromekh. 6 no.3:316-323 \*63. (MIRA 16:5)

1. Moskovskiy energetichaskiy institut.
(Magnetic amplifiers)

UR/0196/65/000/007/A008/A008 I. 16699-66 SOURCE CODE: ACC NR: AR5018675

AUIHOR: Sharokhin, G.I.; Shikhin, 1.Ya.

ORG: none

Card

TITIE: Application of multidigit indexing of passive and active parameters for the calculation of electric circuits of direct current with linear and nonlinear parameters

SOURCE: Ref. zh. Elektrotekhnika i energetika, Abs. 7A66

REF SOURCE: Tr. Mosk. energ. in-ta, vyp. 57, 1964, 27-35

TOPIC TAGS: electric current, linear automatic control, direct current, volt ampere

characteristic Circuit design TRANSIATION: A two-digit indexing of the values with which one has to deal in examining electric circuit processes, indicates not only the location where the pertinent element is switched in, but also the direction of the bypass or of the operation and voltage of the current. Such an indexing is applicable to the calculation of circuits with active and passive elements whose volt-amperecharacteristics are approximated by two direct currents; this indexing allows the application to them of methods used in calculating linear circuits. Also, it greatly decreases the amount of work needed for such calculations. This method is not directly applicable to the calculation of circuits whose characteristics of passive elements are approximated by more than two direct 3 figures and 5 references. B. Yakhinson

SUB CODE:

SUBLY DATE: NOVE

621.3.011.1

ACC NR. AR5018110

SOURCE: UR/0271/65/000/007/A037/A037

SOURCE: Ref. zh. Avtomatika, telemekhanika i vychislitel'naya tekhnika. Svodnyy tom, Abs. 7A271

AUTHOR: Shikhin, A. Ya.

TITLE: Calculating parameters of resonant frequency sensors

CITED SOURCE: Tr. Mosk. energ. in-ta, vyp. 57, 1964, 41-47

TOPIC TAGS: frequency sensor, resonant frequency sensor

TRANSLATION: A low-Q resonant circuit used in automatic-control circuit is analyzed. Formulas for calculating R L C parameters of the resonant circuit are deduced. Experiments have demonstrated adequate accuracy of the calculations. Bib 2, figs 2.

SUB CODE: 09, 13

L 20887-66 EWT(1)/FSS-2/ETC(f)/EWG(m) AT

ACC NR: AP6002524

SOURCE CODE: UR/0286/65/000/023/0031/0032

AUTHORS: Shikhin, A. Ya.; Danil'chenko, V. P.; Sil'vanskiy, I. V.

40

ORG: none

TITLE: Direct current source for feeding a permeameter. Class 21, No. 176629


SOURCE: Byulleten' izobreteniy i tovarnykh znakov, no. 23, 1965, 31-32

TOPIC TAGS: permeameter, permanent magnet, testing device, test equipment, test method, automation

ABSTRACT: This Author Certificate presents a direct current source for feeding a permeameter used for testing permanent materials. The unit is designed to automate the testing process, and contains a direct current generator. The excitation winding of this DC generator is fed from an amplidyne with a fixed negative feedback of the generator voltage (see Fig. 1). The unit also contains a master circular potentiometer with a drive from a nonreversible electric motor with a regulated speed for the purpose of changing the shape and frequency of the test voltage. The unit has a circular rheostat with a sliding contact drive from the nonreversible motor. A push-pull magnetic amplifier provides synchronization

Card 1/2

UDC: 621.318.34:621.318.443



ACC NR: AP7009075 SOURCE CODE: UR/0413/67/000/003/0051/0051

INVENTOR: Shikhin, A. Ya.; Sil'vanskiy, I. V.

ORG: None

TITLE: An automatic magnetizing unit with a noncontact device for shaping the magnetizing current. Class 21, No. 190931 [announced by the Moscow Power Engineering Institute (Moskovskiy energeticheskiy institut)]


SOURCE: Izobreteniya, promyshlennyye obraztsy, tovarnyye znaki, no. 3, 1967, 51

TOPIC TAGS: magnetization, test instrumentation, ferromagnetic material, electric equipment

ABSTRACT: This Author's Certificate introduces an automatic magnetizing unit with a noncontact device for shaping the magnetizing current. The installation contains a master drive, circular potentiometer, magnetic amplifier, amplidyne and magnetizing unit. The device is designed to operate according to the optimum law for variation in the magnetizing current in order to test specimens with any ferromagnetic properties and to provide flexibility in adjustment of the magnetizing current curve. The magnetic amplifier is based on a push-pull adding circuit. Two voltages are fed to the magnetic amplifier is based on a push-pull adding circuit. Two voltages are fed to the magnetic amplifier is based on a push-pull adding circuit. Two voltages are fed to the magnetic amplifier is based on a push-pull adding circuit. Two voltages are fed to the magnetic amplifier is based on a push-pull adding circuit. Two voltages are fed to the magnetic pulse converter through a justable pedestal voltage, and the second from a capacitive pulse converter through a cathode follower.

Card 1/2

UDC: 621.318.34:621.317.443.078



VLOKH, T.V.; SHIKHINA, L. Ye.

Hemagglutination reaction in the diagnosis of dysentery.

Zhur. mikrobiol., epid. i immun. 43 no. 1325-28 Ja 166

(MIRA 19:1)

1. L'vovskiy institut epidemiologii, mikrobiologii i gigiyeny 1 4-ya Detskaya infektsionnaya bol'nitsa. Submitted January 4, 1964.

SHIKHEMASHVILI, N. YA.

Use of penicillin in infectious diseases of the eye. Vest. oft.
29:6, Nov.-Dec. 50. p. 15-8

1. Of the Department of Eye Diseases (Head - Prof. A. N. Shatilov, deceased), Tollisi Nedical Institute.

CIMI 20, 3, March 1951

SHIKHIMASHVILI, N.Ya.

[Tumors of the orbit] Opukholi glaznitay. Tbilisi, Gruzmedgiz.
(MIRA 13:4)

1956. 27 p.

(ORBIT (EYE) -- TUMORS)

SHIKHTHEV, N.I.; PUKHOV, A.P.; SHEVYAKOV, N.N.; KCSHELEV, F.F.; NOVIKOV, M.I.

Continuous action proportioning unit for free flowing materials.

Kauch. i rez. 24 no.5:46-48 My '65. (MTRA 18:9)

1. Nauchno-issledovatel'skiy institut shinnoy promyshlennosti.

S/064/61/000/001/004/011 B110/B215

AUTHORS:

Khmel'nitskaya, I. L., Gutorko, A. V., Shikhireva, L. I.,

Stroyesku, A. K.

TITLE:

Technological problems of synthesizing 2,4- and 2,6-toluylene

diisocyanate

PERIODICAL:

Khimicheskaya promyshlennost', no. 1, 1961, 18-21

TEXT: Diisocyanates required for the production of polyurethane, such as 2,4-toluylene diisocyanate and a mixture of 2,4- and 2,6-diisocyanates, are commercially produced in the following way:

$$H_3C \xrightarrow{NH_2} - NH_2 + 2COC1_2 \longrightarrow H_3C \xrightarrow{N=C=0} - N=C=0 + 4HC1$$

By applying the continuous method, the yield is increased from 65% to 80% as compared to the periodic method. Time-consuming cleaning of the apparatus becomes necessary due to the formation of adhesive resins in the reaction. The authors studied the influence of various factors on dissocyanate and the formation of resin, and the possibilities of using Card 1/6

S/064/61/000/001/004/011 B110/B215

Technological problems of ...

up and removing resin residues for improving the above method. To eliminate side reactions, phosgene treatment is first carried out at low temperatures (0 to  $5^{\circ}$ C). To eliminate the formation of urea derivatives, toluylene diamine is added to a solution of excessive phosgene in o-C<sub>6</sub>H<sub>4</sub>Cl<sub>2</sub> or C<sub>6</sub>H<sub>5</sub>Cl. The following reaction takes place:

$$H_3^{C} \xrightarrow{NH_2} NH_2 + COCl_2 \longrightarrow H_3^{C} \xrightarrow{NH_2 \cdot HCl} NHCOCl$$

By a temperature increase to more than 100°C, diisocyanate forms under the influence of phosgene:

luence of phosgene:
$$H_3C \xrightarrow{NH_2 \cdot HC1} NHCOC1 + COC1_2 \longrightarrow H_3C \xrightarrow{N=C=0} N=C=0 + 4HC1$$

The authors studied the addition of toluylene diamine dissolved (I) or suspended (II) to an inert solvent during the continuous method. In (I) the diamine was dissolved in  ${}^{C}_{6}{}^{H}_{5}{}^{Cl}$ , heated to 90 to 95°C, and added to the solution of phosgene in  ${}^{C}_{6}{}^{H}_{5}{}^{Cl}$  which had been cooled down to -10°C. Card 2/6

S/064/61/000/001/004/011 B110/B215

Technological problems of ...

In (II), diamine dissolved in  ${}^{C}_{6}{}^{H}_{5}{}^{C}l$  was cooled down to  $0^{O}C$  under constant stirring. The limpid liquid changed into a coarse suspension which was pulverized in the ball mill for 7-8 hr. Degree of dispersion and homogeneity of the suspension were studied under the microscope. At  $0^{O}C$ , the suspension was added to the -10°C solution of phosgene; this caused a rise in temperature of up to -5°C. In (I) and (II), phosgene treatment was continued at 120°C. The process was finished after the residue had disappeared. HCl and COCl<sub>2</sub> were blown off by N<sub>2</sub>, and solvent and diisocyanate were separated by fractionation. The isocyanate groups of the final

were separated by fractionation. The isocyanate groups of the remained product were determined by condensation of diethylamine. The nitrogen content of the resin was microanalytically determined according to Dumas. In solution (I) larger solid particles formed in the first part of phosgene treatment, due to partial overheating. For suspension (II), the dependence of resin formation on the size of particles is given in a table. With particle sizes  $< 10\mu$ , the suspension contains no larger solid particles, and the formation of resin is reduced to 15%, as compared to 22 to 32% in solution (I). Aqueous grinding therefore yielded a sufficient degree of dispersion and particle homogeneity at high suspension density. The

Card 3/6

S/064/61/000/001/004/011 B110/B215

Technological problems of...

decomposition of the resin particles into toluylene diamine can only be carried out with aqueous alkali and under pressure, whereas they can be transformed into diisocyanate by distillation at 215°C and 1 to 80 mm Hg in high-boiling naphthene oil. For the latter process, however, an oil that is stable up to 300°C, a high vacuum, and filtering are required. The authors worked without solvents. After the distillation of diisocyanate at 105 to 107°C and 3 to 7 mm Hg, 16.5% of  $N_2$  were microanalytically determined in the resin residue (38 to 40 percent by weight of the distilled diisocyanate) according to Dumas. Diisocyanate vapors were separated from the residue in the vacuum apparatus at 3 to 7 mm Hg and slowly increasing temperature. At 170 to 180°C it puffed up and hardened. Vapor separation stopped between 280 and 300°C. The residue, a dry, brittle, porous substance, was easily removable after cooling it in the  $N_2$ -current. Its nitrogen content was 16.4%. The authors assume that the original residue, besides the not distilled monomers, also contained the following dimer:

Card 4/6

S/064/61/000/001/004/011
Technological problems of...
B110/B215

$$0=C=N$$

$$H_3C$$

$$-N$$

$$C$$

$$N$$

$$-CH_3$$
or

which decomposes into the monomer at 175°C. The second residue consists of high-polymer compounds. There are 1 table and 6 references: 2 non-Soviet-bloc.

Card 5/6

echnological problems of		S/064/ B110/I	/61/000/001 3215	/004/011	
Legend to the Table: yield of disocyanate and resin particles by adding emulsions, 1) particle size $\mu$ , 2) yield, $\pi$ , 3) toluylene			2) Bux		
		Размер частиц µ	3) толуиленди-	4) смолнстых примесей.	
iisocyanate, 4) resin particles, ) mixture of 2,4- and 2,6-toluylene	5) Смесь 2,4- и 2.6-толуилендиаминов				
iamine, 6) toluylene diamine.	'n		79,8 70,0 65,6	15,1 21,8 24,4	•
			2.4-Толуилендиам	кн	** ** **
		< 10 <300	78,3 67,0	15.2 19,1	
•		· · · · · · · · · · · · · · · · · · ·			
		,			
		•			
Card 6/6	•				
aru 0/0	•	10 A April 10			

PERSHIN, G.N.; BELIKOV, G.P.; YAKOVLEVA, A.I.; SHIKHIREVA, M.V.

Viral hepatitis in mice as a model for chemotherapeutic research. Vop. virus 8 no.5:574-579 S-0'63 (MIRA 17:1)

Vsesoyuznyy nauchno-issledovatel'skiy khimiko-farmatsevtiches-kiy institut imeni Sergo Ordzhonikidze, Moskva.

YAKOVIEVA, A.I. (Moskva); PERSHIN, G.N. (Moskva); BELIKOV, G.P. (Moskva); SHIKHIREVA, M.V. (Moskva)

Morphological characteristics of viral hepatitis in mice. Arkh. pat. 25 no.5:67-71 163. (MIRA 17:2)

1. Iz otdela khimioterapii (zav. - chlen-korrespondent AMN SSSR prof. G.N. Pershin) Vsesoyuznogo nauchno-issledovatel'-skogo khimiko-farmatsevticheskogo instituta imeni S. Ordzhonikidze.

YAKOVLEVA, A.I. (Moskva); SHIKHIREVA, M.V. (Moskva); PERSHIN, G.N. (Moskva); MOSKALENKO, N.Yu. (Moskva)

Morphological characteristics of a model of cutaneous leischmaniasis in white mice. Arkh. pat. 27 no.4:52-57 '65. (MIRA 18:5)

1. Otdel khimioterapii (zav. - chlen-korrespondent AMN SSSR prof. G.N.Pershin) Vsesoyuznogo nauchno-issledovatel skogo khimiko-farmatsevticheskogo instituta imeni Ordzhonikidze.

The strain of the control of Table 1911 Table 1911 to the control of the control

SHIKHIYEV, Fund Makeimovich, kandidat tekhnicheskikh nauk; ORDELLI, Mikhail

Fred yevich, inzhener; TSETTLIN, Grigoriy Yul'yevich, inzhener;

PLAKIDA, M.E., redaktor; SAFOROV, P.V., redaktor izdatel'stve;

TIKHONOVA, Ye.A., tekhnicheskiy redaktor

[Experience in building hydraulic structures] Opyt stroitel'stva
gidrotekhnicheskikh sooruzhenii. Moskva, Izd-vo "Morskoi transport,"

(Hydraulic engineering)

(Hydraulic engineering)

SHIKHIYEV, F.M., kand.tekhn.nauk, dotsent

Experimental investigations of screen piles. Nauch.trudy OIMF no.13:33-54 157.

(Piling (Civil engineering))

SHIKHIYEV, F.M., kand.tekhn.nauk, dotsent; REUT, V.I., kand.tekhn.nauk, dotsent

Experimental investigations of new types of loading and unloading equipment. Nauch.trudy OIIMF no.13:55-79 '57.

(MIRA 11:11)

(Loading and unloading)

BRYUM, Abran Isayevich, inzh.; VORONOV, Petr Andreyevich, dotsent, kand.

tekhn.nauk [deceased]; GINSBARG, Ruvin Izrailevich, kand.tekhn.nauk;

KUTEYNIKOV, Aleksandr Nikolayevich, inzh.; FEDOROV, Aleksandr

Timofeyevich, prof. [deceased]; SHAPOVALOV, Petr Borisovich, inzh.;

SHIKHIYEV, Fuad Maksimovich, dotsent, kand.tekhn.nauk; YAVLEHSKIY,

S.D., retsenzent; KRUGLENKO, N.K., retsenzent; MATLIN, G.M., kand.

tekhn.nauk, red.; KSENOFONTOVA, Ye.F., red.izd-va; TIKHONOVA, Ye.A.,
tekhn.red.

[Sea ports and harbor facilities] Morskie porty i portovye sooruzheniia. Moskva, Izd-vo "Morskoi transport," 1959. 519 p. (MIRA 12:12)

(Harbors)

SHIKHIYEV, F.M., kand. tekhn. nauk; TSEYTLIN, G.Yu., inzh.

Using precast elements in constructing wharves. Hov. tekh. mont. 1
spets. rab. v stroi. 21 no.2:22-24 F '59.

(Precast concrete construction) (Wharves)

SHIKHIYEV, Fuad Maksimovich; YEROFKYEV, Nikolay Ivanovich; GINSBARG,
Ruvim Izrailevich; TSEYTLIN, Grigoriy Yul'yevich; OBERMEYSTER,
A.M., red.; MARCHUKOVA, H.G., red. izd-va; TIKHONOVA, Ye.A.,
tekhn. red.

[Organization and equipment of sea ports] Ustroistvo i oborudovanie morskikh portov. Moskva, Izd-vo "Morskoi transport,"
(MIRA 14:5)

(Harbor)

Operating 13-19 '61.	loads acting (	on mooring	structure gineering-	s. Gidro _Researc	tekhnika no (MIRA 19 h)	.1: 5:3)	
					•		
						:	

MAZUR, V.Yu.; SHIKHIYEV, F.M.

Experimental model studies on mooring loads. Gidrotekhnika no.l:
(MIRA 15:3)
19-25 '61.
(Anchorage)(Hydraulic engineering—Research)

HIKHIYEV, F.M.  Lightweight design for elements of bracing pert structures employing reinforcement of the fill. Gidrotekhnika no.2:72-79 162.  (MIRA 16:5)				
(Earth pressure)	(Retaining w	alls)		
		•		
		<u>-</u>		


Studies of soil deformations and stress. Gidrotekhnika no.2:100-110 (MIRA 16:5)


SHIKHIYEV, F.M.

Generalized soil stress. Gidrotekhnika no.2:110-118 '62.

(MIRA 16:5)

(Soil mechanics)






SHIKHIYEV, F.M.; MAZUR, V.Yu. Stresses originating during the approach of vessels to the mooring bollards of locks. Trudy Otd. energ. Dag. fil. AN

(MIRA 17:7) SSSR. 1 no.1:13-24 162.

ACC NR. AR6035388 (N) SOURCE CODE: UR/0398/66/000/009/B002/B002		
AUTHOR: Shikhiyev, F. M.; Kovtun, V. V.		
TITLE: Investigation of soils with the aid of a bulk shear instrument		
SOURCE: Ref. zh. Vodnyy transport, Abs. 9B5	,	
REF. SOURCE: Nauchn. tr. Upr. uchebn. zavedeniy M-va morsk. flota SSSR, no. 1, 1965, 103-106		
TOPIC TAGS: soil mechanics, shear strength, measuring instrument		
ABSTRACT: bulk shear instrument in which, unlike in three-axis instruments, the investigated soil is in a state condition of plane deformation, was developed at the soil Laboratory of OIIMF at the suggestion and under the leadership of F. M. Shikhnev. The use of the bulk-shear instrument makes it possible to obtain very good agreement between the results of laboratory investigations and the natural operating state of the soil. The construction diagram of the instrument is presented, and the procedures and sequence of the experiments and of the data reduction are described. 2 illustrations. [Translation of abstract]		
SUB CODE: 08	_	
UDC: 624.131.3		
Card 1/1		

APPROVED FOR RELEASE: 08/25/2000 CIA-RDP86-00513R001549420003-3"



SHIKHEEV, I. A.


 $\subset A$ 

Electrolytic hydrogenation of acetals with a triple bond.

1. A. Shikhiev (Azerbaidzhan Acad. Sci.). Zhur. Obskehel Khim. (J. Gen. Chem.) 20, 839-47(1959).—To 40 g. Mer-COHC: and 30 g. Mer-NPh was added 35 g. Mer-OH-Ici in 1.5 hrs. at -10°, and the mixt. stirred 3 hrs. at room temp.; the upper layer yielded 22.97% MerC(C: CH)-om temp.; the upper layer yielded 22.97% MerC(C: CH)-OHOME (1), b. 109-12°, dig 0.8909, #B 1.4250, yellowed on standing. EtOCH<sub>2</sub>CI similarly gave 27.87% MerC(C: CH)OCH<sub>2</sub>OE (II), L. 120-2°, dig 0.8816, #B 1.4200; iso-PrOCH<sub>2</sub>OE (II), L. 120-2°, dig 0.8816, #B 1.4200; iso-PrOCH<sub>2</sub>OE (II), D. 120-2°, dig 0.8816, #B 1.4200; iso-PrOCH<sub>2</sub>OE (III), D. 120-2°, dig 0.8816, #B 1.4200; iso-MerC(H<sub>2</sub>OH<sub>2</sub>OE) and the standard and the

CONFUSION CONTRACTOR DESCRIPTION OF THE PROPERTY OF THE PROPER

hrs., tonowed by standing overnight, gave 20.8% McEtt (C: CH)OCH<sub>2</sub>OMe (VI), b. 132-5<sup>3</sup>, d<sub>4</sub><sup>2</sup> 0.8887, #4<sup>2</sup> 1.4248; McEtC(C: CH)OCH<sub>2</sub>OE (VII), b. 147-50<sup>6</sup>, d<sub>4</sub><sup>2</sup> 0.8899, #4<sup>6</sup> 1.4266, was obtained similarly in 29.28% yield. Electrolytic reductions were run in a divided cell, with Ni wire anode, silvered Cu cathode, 1% aq. EtOH-NaOH catholyte, and satd. NaOH anolyte. Under these conditions the following vinylandigs were obtained: from I, 42.19%, b. 100-4°, d<sub>4</sub><sup>2</sup> 0.8020, #4<sup>6</sup> 1.4160 (the same product obtained by condensation of Mc<sub>2</sub>C(OH)CH: CH, with ClCH<sub>2</sub>OMe in the presence of Mc<sub>2</sub>NPh at -6°, b. 108-11°, d<sub>4</sub><sup>2</sup> 0.8912, #4<sup>6</sup> 1.4158); from II, 62.18%, b. 105-8°, d<sub>4</sub><sup>2</sup> 0.8825, #4<sup>6</sup> 1.4125; from III, 63.8%, b. 110-23°, d<sub>4</sub><sup>2</sup> 0.8812, #4<sup>6</sup> 1.4114; from IV, b. 132-5°, d<sub>4</sub><sup>2</sup> 0.812, #4<sup>6</sup> 1.4090 (54.37%); from V, b. 148-51°, d<sub>4</sub><sup>2</sup> 0.812, #4<sup>6</sup> 1.4103 (32.88%); and from VII, b. 121-4°, d<sub>4</sub><sup>2</sup> 0.812, #4<sup>6</sup> 1.4100. The vinyl analog of VII was also obtained by condensation at -8° of ClCH<sub>2</sub>OE with McEtC(OH)CH: CH<sub>3</sub> and powd. KOH in Et<sub>2</sub>O; the product b. 137-40°, d<sub>4</sub><sup>2</sup> 0.8406, #4<sup>6</sup> 1.4184. The vinyl derivs, were stable on storage.



# SHIKHIYEY I.A.

USSR/ Chemistry - Synthesis

Pub. 40 - 20/22Card

Shostakovskiy, M. S.; Shikhiev, I. A.; and Kochkin, D. A. Authors

Synthesis and conversions of oxygen-containing silicon-organic com-Title

pounds. Part 1 .- Synthesis of silicon-organic acetals

Izv. AN SSSR. Otd. khim. nauk 5, 941-944, Sep-Oct 1953 Periodical

A new synthesis of O-containing silicon-organic compounds, based on the reaction of vinyl ethers and silanols, is discussed. It was established Abstract


for the first time that triethylsilanol condenses with vinylbutyl and vinylisobutyl ethers in conditions analogous to corresponding syntheses with organic alcohols. The synthesis of hitherto unknown nonsymmetrical butyl- and isobutyltriethylsilaneacetals, is described. A new method for the derivation of various silicon-organic acetals, is pre-

sented. Three USSR references (1933-1952).

Academy of Sciences, Institute of Organic Chemistry Institution :

December 23, 1952 Submitted

THE PROPERTY OF THE PROPERTY O	A THE RECEIPED TO THE CONTROL OF THE PROPERTY	W-100
SHIKHIYEV, I-A.		
	Synthad	
1	Synthesis and transformations of oxygen-containing	
<u>.</u>	silicorganic compounds. Synthesis of methyl, ethyl, and isopropyl triethylsilano acetals. M. F. Shostakovskii, K. A. Andrianov, I. A. Shikhiev, and D. A. Kochkin. Doklady.  Heating 33 g. EtsiOH; 19 g. McOCH; CH. and D. O. Society.  30% HCI in seried.	
	Citto is a mediate time by his at any	
	Et. SiOH and 36 g. BtOCH: CH: wat added a co. To 33 g.	
, -	SiOH with and Similarly is Propulation	
	tube at 05° gave 42° MeCHOCHAT S.5 hrs. in a scaled	
	一、产生、主、产生、产品、产品、产品、产品、产品、产品、产品、产品、产品、产品、产品、产品、产品、	
	INGL. Organis Cliemisty Inv. N.D. Zeliuskego,	
	ING. Organis Chemisky Inv. N.D. Zeliuskego, Acadi Soenei, Ussa:	
<b>元当后的《北京》中华第四年为10月的10日的</b>	地名西班西比亚拉伯拉 医克拉克氏试验 医复数线性 化聚基苯酚 医多种性 医电影 医电影 医电影 医多种性 医多种性 医多种	Bartanian Salah di Barania



#### CIA-RDP86-00513R001549420003-3 "APPROVED FOR RELEASE: 08/25/2000

SHIKHIYEV, I.A.

USSR/Organic Chemistry - Synthetic Organic Chemistry, E-2

Abst Journal: Referat Zhur - Khimiya, No 19, 1956, 61593

Shostakovskiy, M. F., Shikhiyev, I. A. Author:

None Inst. Org. Chem in N.D. Zelinsky, AS USSE Institution:

Investigations of the Syntheses and Conversions of Organosilicon Compounds. Communication I. Synthesis of the Vinyl Ether of )-Title:

hydroxypropyltrimethylsilane

Original

Izv. AN SSSR, otd. khim. n., 1954, No 4, 745-747 Periodical:

Abstract: Using \( \gamma\)-hydroxypropy trimethylsilane (I) as an example the possibility has been ascertained of vinylating organosilicon alcohols.

I was prepared by passing for 2.5 hours gaseous thylene oxide (2 mol) into a cooled to -6° Grignard reagent (from 1 g-atom Mg in 800 ml solute are and 1 mol  $\alpha$ -chloromethyl trimethylsilane), yield 77.3%, BP 62-63°/10 mm n<sup>2</sup>°0 1.4298, df 0.8408. The vinyl ether of Y-hydroxypropyl trimethylsilane CH<sub>2</sub> = CH-OCH<sub>2</sub>CH<sub>2</sub>CH<sub>2</sub>Si (CH<sub>3</sub>)<sub>3</sub>

(II) obtained on heating in autoclave (8 hours, 1800) a reaction

Card 1/2

SHIP SHOSTAKOVSKIY, M.F.; SHIKHIYEV, I.A.; VIASOV, V.M.; HELYAYEV, V.I.

Synthesis of vinylisopropyl, vinyldibutyl and vinyldiamyl ethers and their conversions. Dokl. AN Azerb. SSR 10 no.7:473-482 '54.

(MLRA 8:10)

1. Predstavleno deystvitel'nym chlenom Akademii nauk Azerbaydshanskoy SSR Yu.G. Mamedaliyevym.


(Vinyl polymers)

SHOSTAKOVSKIY, M.F.; SHIKHIYEV, I.A.; RELYAYEV, V.I.

Investigation in the field of synthesis of derived tertiary unsaturated alcohols. Dokl.AN Azerb.SSR 10 no.11:759-765 '54.

(MIRA 8:10)

1. Predstavleno deystvitel'nym chlenom Akademii nauk Azerbaydzhanskoy SSR Yu.G.Mamedaliyevym. (Alcohols)



SHIKHIYEV, Ibragim Abasovich Name:

Investigation in the field of the Dissertation:

synthesis and transformations of secondary, tertiary silico-organic alcohols and silanols

Doc Chem Sci Degree:


[Not indicated] Affiliation:


28 Jun 55, Council of Inst of Organic Chemistry, Acad Sci USSR

Defense Date, Place:

9 Mar 57 Certification Date:

Source: BMVO 13/57





SHOSTAKOVSKIY, M.F.; SHIKHIYEV, I.A.; KOMAROV, N.V.

Research in the field of synthesis and conversion of silicon organic compounds containing oxygen. Dokl.AN Azerb.SSR 11 no.11; 757-763 '55. (MIRA 9:5)

1. Institut organicheskoy khimii imeni N.D. Zelinskogo AN SSSR.
Predstavleno deystvitel'nym chlenom AN Azerbaydzhanskoy SSR Yu.G.
Mamedaliyevym.
(Silicon organic compounds)


SHOSTAKOVSKIY, M.F.; KOCHKIN, D.A.; SHIKHIYEV, I.A.; VLASOV, V.M.

Investigation in the field of oxygenated silicon organic compounds.

Part 7. Synthesis and certain conversions of silanols. Zhur.ob.

Khim. 25 no.3:622-626 Mr '55. (MLRA 8:7)

1. Institut organicheskoy khimii Akademii nauk SSSR. (Silanol)



SHOSTAKOVSKIY, M.F.; SHIKHIYEV, I.A.; KOMAROV, M.V.

Investigations in the field of the synthesis and conversion of oxygen-containing silicon organic compounds. Report no.3: Synthesis and conversion of some vinyl esters of Y-hydroxipropyltrimethyland methyldiethylsilanes. Izv. AN SSSR. Otd. khim. nauk no.12:1493-1499 D 156. (MIRA 10:4)

1. Institut organicheskoy khimii imeni N.D. Zelinskogo Akademii nauk SSSR.

(Silane)

SHIKHIYEV, I

USSR/Organic Chemistry - Synthetic Organic Chemistry

E-2

Abs Jour

: Referat Zhur - Khimiya, No 2, 1957, 4469

Author

: Shostakovskiy, M.F., Shikhiyev, I.A., Komarov, N.V.

Inst

: Academy of Sciences Azerbaydzhan SSR

Title

: Investigations of the Synthesis and Conversions of

Cxygen-Containing Organosilicon Compounds

Orig Pub

: Dokl. AN AzerbSSR, 1956, 12, No 3, 177-181

Abstract


: On heating (60-65°, 35 hours) equimolecular amounts of vinyl ether, gamma-hydroxypropyl-trimethylsilane and corresponding organic acid (glacial CH3COOH, propionic, isobutyric) and subsequent fractionation in vacuum, were obtained the following partial organosilicon acetals  $\text{CH}_3\text{CH}(\text{OCOR})\text{O(CH}_2)_3\text{Si(CH}_3)_3$  (listing consecutively R,

yield in %, BP in  ${}^{\circ}$ C/mm,  ${}^{\circ}$ C/m,  ${}^{\circ}$ C);  ${}^{\circ}$ CH<sub>3</sub>, 59.5, 92-93/8, 1.4218, 0.9027;  ${}^{\circ}$ C<sub>2</sub>H<sub>5</sub>, 73.15, 99-100/7, 1.4242, 0.8979; (CH<sub>3</sub>)<sub>2</sub>CH, 64.0, 110-111/7, 1.4262, 0.8935.

 $(CH_3)_2$ CH, 64.0,

Card 1/1

- 110 -



E-2

# SHIKH IYEV, IA.

USSR/Organic Chemistry - Synthetic Organic Chemistry

: Referat Zhur - Khimiya, No 2, 1957, 4468

Abs Jour : Shikhiyev, I.A., Komarov, N.V.

Author

: Investigations of the Synthesis and Conversions of Oxygen-Containing Organosilicon Compounds. Synthesis Inst Title

of Organosilicon Acetals on the Basis of Vinyl Ether of Gamma-Hydroxypropyl-Trimethylenesilane, Organosilicon

Alcohols and Silanol.

: Dokl. AN SSSR, 1956, 108, No 2, 279-281

Orig Pub By heating equimolecular amounts of CH2 CHO(CH2)3Si(CH3)3

Abstract


and an organosilicon alcohol (C2H5)3SiOH, (CH3)3SiCH2OH

or (CH3) Si(CH2)3 OH with an addition of 30% solution of

HCl, at 65° for 30 minutes, there have been synthesized

Card 1/2

\_ 108 -



# SHIKHIYEV, I.A.; KAYUTENKO, L.A.

Studies in the field of synthesis and transformations of unsaturated organosilicon compounds. Report No.5: Synthesis of mixed diacetylene organosilicon glycols. Izv. AN SSSR. Otd. khim. nauk no.8:991-993 (MIRA 11:2)

1. Institut organicheskoy khimii im. N.D. Zelinskogo AN SSSR. (Glycols) (Silicon ogranic compounds)

SHIKHIYEV, I.A.; SHOSTAKOVSKIY, M.F.; KOMAROV, N.V.

Synthesis and transformation of silicon organic compounds containing oxygen. Report No.8: Interaction of vinyl ethers with silanes and /2-alcohols containing silicon. Izv. AN SSSR. Otd. khim. nauk no.9:1132-1133 S 157. (MIRA 10:12)

1. Institut organicheskoy khimii im. N.D. Zelinskogo AN SSSR.
(Vinyl ether) (Silane) (Alcohols)


SHIKHIYEV, I.A.; SHOSTAKOVSKIY, M.F.; KOMAROV, N.V.; KAYUTENKO, L.A.


Studies in the field of synthesis and transformations of unsaturated silicon organic compounds. Report No.2: Synthesis of

silicon containing tertiary triatomic alcohols of the acetylene series. Izv. AN SSSR. Otd. khim. nuak no.9:1139-1141 S 57. (MIRA 10:12)

1. Institut organicheskoy khimii im. N.D. Zelinskogo AN SSSR.

(Silicon organic compounds) (Alcohols)





62-58-3-20/30

AUTHORS:

Shikhiyev, I. A. Kayutenko, L. A., Lukevits, E.

TITLE:

Investigations in the Domain of the Synthesis and Reactions of Unsaturated Organosilicon Compounds (Issledovaniya v oblastibinteza i prevrashcheniy nepredel'nykh kremneorganicheskikh soyedineniy) Communication 9: The Synthesis of Mixed Organosilicon Glycob of the Diacetylene Series (Soobshcheniye 9: Sintez smeshannykh kremneorganicheskikh glikoley diatsetilenovogo ryada)

Izvestiya Akademii Nauk SSSR, Otdeleniye Khimicheskikh Nauk, PERIODICAL:

1958, Nr 3, pp. 363 -364 (USSR) and the grant of the contract of the contract

ABSTRACT:

The present paper belongs to thos investigations dealing with the development of the chemistry of ternary acetylene alcohols containing silicon in their composition. The authors describe two reprentatives of the mixed diacetylene glycols which were synthesized according to the following scheme:

Card 1/3

62-58-3-20/30

Investigations in the Domain of the Synthesis and Reactions of Unsaturated Organosilicon Compounds. Communication 9: The Synthesis of Mixed Organosilicon Glycols of the Diacetylene Series

(R is equal to  $CH_3$ ,  $R' = C_2H_5$ ;  $C_3H_7$ )

According to this method another synthesis was also perfored which led to the production of a corresponding organosilicon diacetylene glycol. See table. In a similar manner a method for the production of organosilicon alcohols was worked out. There are 1 table and 7 references, 7 of which are Soviet.

Card 2/3

62-58-3-20/30

Investigations in the Domain of the Synthesis and Reactions of Unsaturated Organosilicon Compounds. Communication 9: The Synthesis of Mixed Organosilicon Glycols of the Diacetylene Series

ASSOCIATION: Institut organicheskoy khimii im. N. D. Zelinskogo Akademii

nauk SSSR

(Institute for Organic Chemistry imeni N. D. Zelinskiy,

AS USSR)

SUBMITTED:

October 10, 1957

Card 3/3

SHIKHIYEV, I.A.; SHOSTAKOVSKIY, M.F.; KAYUTENKO, L.A.

Investigations in the synthesis and conversion of unsaturated silicon erganic compounds. Dokl. AN Azerb.SSR 14 no.9:687-689 (MIRA 11:10)

1. Institut organicheskoy khimii AN SSSR im. N.D.Zelinskogo i Institut nefti AN AzerSSR. Predstavleno akademikom AN AzerSSR Yu.G. Mamedaliyevym.

(Silicon organic compounds)

5(3) AUTHORS:

ż.

Shikhiyev, I. A., Komarov, N. V.,

SOV/74-27-12-4/4

Aslanov, I. (Baku)

TITLE:

Synthesis and Some Transformations of Organic and Organosilicon Acetals (Sintez i nekotoryye prevrashcheniya organicheskikh

i kremniyorganicheskikh atsetaley)

PERIODICAL:

Uspekhi khimii, 1958, Vol 27, Nr 12, pp 1504 - 1517 (USSR)

ABSTRACT:

In the present paper the authors carried out a comparative estimation of organic and organosilicon acetals by comparing their properties, conditions of synthesis and some transformations based upon acetylene, aldehydes, organic and organosilicon alcohols and silanols. Comparing the methods of synthesis of organic acetals with those of organosilicon acetals the former are stated to show a greater variety. Investigations in the field of synthesis of acetals were started on the basis of acetylene as well as of alcohols containing 1, 2, and 3 carbon atoms in the presence of various catalysts. On the strength of comprehensive investigations it was found that vinyl ethers are valuable initial substances for various syntheses. It was found that apart from acetylene alcohols, also acetylene glycols are good

Card 1/5

sov/74-27-12-4/4

Synthesis and Some Transformations of Organic and Organosilicon Acetals

initial substances for the synthesis of acetylene acetals. As far as the saturated glycols are concerned it is known (Refs 24 and 25) that some ethylene glycol derivatives have been widely applied to the field of preparative organic chemistry and various industries. The investigations of the synthesis of cyclic acetals and their application are of great theoretical and practical importance. Silicon containing acetals take a special position (Refs 38 - 41). Organic acetals are colorless, transparent liquids smelling like ether. It is possible to explain the formation of organic acetals in their synthesis from vinyl ether and alcohols on the basis of Shostakovskiy's oxonium theory (Refs 13, 42 - 45). It was shown (Refs 74 and 23) that on heating vinyl ether with alcohol in the autoclave corresponding acetals are formed also without a catalyst. Organic acetals have particular properties which are due to their structure. They are easily formed and are inclined to decompose. It is a well-known fact that (Refs 13, 15, 16) mixed alkyl acetals disproportionate on heating and that they form corresponding symmetric acetals. When heated under atmospheric pressure

Card 2/5

sov/74-27-12-4/4

Synthesis and Some Transformations of Organic and Organosilicon Acetals.

alkyl aryl acetals are split off and phenol is separated (Ref 60). Thus a new method of indirect synthesis of different vinyl ethers by means of distillation of alkyl aryl acetals under atmospheric pressure was discovered. This method is the basis of the indirect synthesis of vinyl ethers of a series of unsaturated tertiary and aliphatic alcohols the synthesis of which can hardly be sarried out in a different way. In 1953 the chemistry of organosilicon acetals was introduced for the first time on the basis of vinyl alkyl ether and trialkylsilanols (Refs 61, 62). Later on this reaction was also applied to other representatives of trialkylsilanols (Refs 62 - 65), alkyl aryl silanols (Refs 38, 40, 66 68), dialkyl silandiols (Ref 69) and organosilicon alcohols (Refs 38, 70 - 72). According to their structure, organosilicon acetals are divided into symmetric and asymmetric ones. In 1954 the authors of the present paper obtained acetals from a silicon containing alcohols and vinyl ethers (Refs 38, 40). In 1955 the authors obtained organosilicon acetals on the basis of organosilicon vinyl ethers and alcohols as well as silanols; the mentioned acetals contained

Card 3/5

Synthesis and Some Transformations of Organic and Organosilicon Acetals

SOV/74-27-12-4/4

silicon atoms in both alcohol radicals (Refs 74, 76). Organosilicon acetals are colorless, transparent and oily liquids smelling like ether. They are easily soluble in organic solvents and not soluble at all in water. . compared to organic acetals their freezing point is much lower and they are most resistant. Based upon Shostakovskiy's oxonium theory (Refs 13, 42, 43) it may be assumed that the formation of organosilicon acetals is due to an ion mechanism. Their chemical properties remind us of organic acetals. Nevertheless, new peculiar properties are found in those compounds due to an interaction of silicon and other atoms forming the molecule. It is worth while to carry out further investigation of organosilicon acetals. With respect to their reactivity they are related with their organic analogs and they could, therefore, easily be used as valuable initial substances for numerous transformations which have been well investigated in the case of corresponding organic acetals but unknown in the case of organosilicon acetals.

Card 4/5

Synthesis and Some Transformations of Organic and Organosilicon Acetals

SOV/74-27-12-4/4

There are 78 references, 61 of which are Soviet.

Card 5/5

USCOMM-DC-60,557

AUTHORS:

Shostakovskiy, M. F., Kulibekov, M. R., Shikhiyev, I. A.

TITLE:

Investigation of the Substitution Reaction of Oxy Radicals by Radicals of Organomagnesium Compounds (Issledovaniye reaktsii obmena oksiradikalov na radikaly magniyorganicheskikh soyedineniy) III. Conversion of Organomagnesium Compounds With Mixed Organosilicon Acetals (III. Vzaimodeystviye magniyorganicheskikh soyedineniy so smeshannymi kremniyor-

ganicheskimi atsetalyami)

PERIODICAL:

Zhurnal coshchey khimii, 1958, Vol. 28, Nr 6, pp. 1539-1542

(USSR)

ABSTRACT:

In earlier papers (Ref !) the authors investigated the effect of the Grignard reagents with respect to the mixed and asymmetric organic acetals, and they found that in the mixed acetals the oxy radicals are in the first place substituted by the Grignard radical under the formation of ethers. With respect to the substitution of the oxy radicals in the symmetric acetals the following sequence shows up: OAr > OAlk > OCH<sub>2</sub>C<sub>6</sub>H<sub>5</sub>. This rule was explained by the presence of a

Card 1/4

Investigation of the Substitution Reaction of Oxy Radicals by Radicals of Organomagnesium Compounds. III. Conversion of Organomagnesium Compounds With Mixed Organosilicon Acetals

TANK TENERAL PER PERSONAL PERS

certain bond position, by which one of the oxy radicals becomes more mobile. It was of interest to investigate an analogous reaction for mixed organosilicon acetals (Ref 2) and to explain the influence of silicon on the mobility of the oxy radical in the acetals. Different from the aliphatic-..aromatic acetals the aliphatic ones easily are subjected to a symmetrization. The mixed organosilicon compounds are accompanied by a number of reactions in the symmetrization, decomposing on thermal treatment. On using the Grignard reagent with mixed organosilicon acetals the authors arrived at the conclusion that the oxy radical containing a silicon atom, is suited for substitution, independent of the fact whether it is directly connected with the oxygen or whether it is in a remote position. In either case the corresponding ethers are obtained (see scheme). Thus it was found that on the action of the Grignard reagent on the organosilicon acetals the following sequence of conversion is found:

Card 2/4

Investigation of the Substitution Reaction of Oxy Radicals by Radicals 30W79-28-6-22/63 of Organomagnesium Compounds. III. Conversion of Organomagnesium Compounds With Mixed Organosilicon Acetals

OSi 
$$CH_3$$
  $CH_3$   $CH_2$   $CH_2$   $CH_3$   $CH_2$   $CH_3$   $CH_2$   $CH_3$   $CH_3$   $CH_2$   $CH_3$   $CH_3$   $CH_3$   $CH_3$   $CH_4$   $CH_5$   $CH_$ 

There are 11 references, 11 of which are Soviet.

ASSOCIATION: Institut organicheskoy khimii Akademii nauk SSSR i Azer-

baydzhanskiy sel'skokhozyaystvennyy institut (Institute of Organic Chemistry, AS USSR and Azerbaydzhan Institute of Agri-

SUBMITTED: May 2c, 1957

Card 3/4

Investigation of the Substitution Reaction of SOV/79-28-6-22/63 Oxy Radicals by Radicals of Organomagnesium Compounds. III. Conversion of Organomagnesium Compounds With Mixed Organosilicon Acetals

- 1. Grignard reagents---Chemcial reactions 2. Organic acids--Chemical reactions
- 3. Silicon compounds (organic)—Chemical reactions

THE WAY OF SHARE STREET STREET, BUT SHOW HE WAS A SHARE THE SHARE SHARE

Card 4/4

5(3)

SOV/62-59-1-23/38 AUTHORS:

Khomutov, A. M., Shikhiyev, I. A., Komarov, N. V., Alimov, A. P.

TITLE:

Investigations in the Field of Chemical Transformations of Unsaturated and High-Molecular Compounds (Issledovaniya v oblasti khimicheskikh prevrashcheniy nepredelinykh i vysokomolekulyarnykh soyedineniy) Communication 8. polymerization of  $\gamma$ -Silicon—Containing Vinyl Ethers and Methyl Mcthacrylate (Soobshcheniye 8. Sopolimerizatsiya γ-kremnesoderzhashchikh prostykh vinilovykh efirov i metil-

metakrilata)

CHESSEN BREATH BEAUTH FERENCE AND ARREST HER STREET

PERIODICAL:

Izvestiya Akademii nauk SSSR. Otdeleniye khimicheskikh nauk,

1959, Nr 1, pp 140 - 143 (USSR)

ABSTRACT:

In the present paper the authors investigated the copolymerization of methyl methacrylate and vinyl ether which contain the silicon atom in  $\gamma$ -position with respect to ethereal oxygen. Ether of \gamma-hydroxy-propyl-trimethyl silane (Ref 1) and  $\gamma$ -hydroxy-propyl-methyl-diethyl silane (Ref 2) were used. These compounds were copolymerized in

Card 1/3

the presence of benzoyl peroxide and dinitrile of azoiso-